


Pre-insulated Terminals

Ring Terminals

Material: Copper
Insulation: Polyvinyl Chloride
Max. elec. rating: ■ 19 amp
■ 27 amp
■ 48 amp

600 volts 75°C

RoHS compliant



Wire Range mm ² (AWG)	Part No.	Dimensions mm					
		D1	D3	D4	L	L1	D2
0.5-1.5 (22 - 16)	32RER	1.8	5.5	4.3	13.7	10	3.2
	37RER	1.8	6.6	4.3	15.5	10	3.7
	43RER	1.8	8.0	4.3	16.2	10	4.3
	53RER	1.8	8.0	4.3	16.7	10	5.3
	65RER	1.8	11.0	4.3	20.4	10	6.5
	85RER	1.8	12.0	4.3	20.2	10	8.5
1.5-2.5 (16 - 14)	10RER	1.8	14.5	4.3	25.1	10	10.0
	32BER	2.3	5.5	4.8	15.5	10	3.2
	37BER	2.3	6.6	4.8	15.6	10	3.7
	43BER	2.3	8.0	4.8	15.9	10	4.3
	53BER	2.3	8.0	4.8	16.9	10	5.3
	65BER	2.3	10.5	4.8	20.8	10	6.5
4-6 (12 - 10)	85BER	2.3	12.0	4.8	21.4	10	8.5
	10BER	2.3	14.5	4.8	23.6	10	10.0
	32YER	3.5	7.2	6.5	22.2	13.5	3.2
	37YER	3.5	7.2	6.5	22.2	13.5	3.7
	43YER	3.5	9.5	6.5	22.2	13.5	4.3
	53YER	3.5	9.5	6.5	22.2	13.5	5.3
	65YER	3.5	11.0	6.5	23.5	13.5	6.5
	85YER	3.5	14.0	6.5	27.0	13.5	8.5
	10YER	3.5	15.0	6.5	30.0	13.5	10.0
	12YER	3.5	19.0	6.5	30.0	13.5	13.0

Pack Quantity: 100




Fork Terminals

Material: Copper
Insulation: Polyvinyl Chloride
Max. elec. rating: ■ 19 amp
■ 27 amp
■ 48 amp

600 volts 75°C

RoHS compliant



Wire Range mm ² (AWG)	Part No.	Dimensions mm					
		D1	D3	D4	L	L1	D2
0.5-1.5 (22 - 16)	32RF	1.8	5.7	4.3	15.3	10	3.2
	37RF	1.8	6.4	4.3	15.3	10	3.7
	43RF	1.8	6.4	4.3	15.8	10	4.3
	53RF	1.8	7.5	4.3	16.4	10	5.3
	65RF	1.8	8.5	4.3	19.7	10	6.5
	32BF	2.3	6.0	4.8	16.0	10	3.2
1.5-2.5 (16 - 14)	37BF	2.3	6.4	4.8	15.7	10	3.7
	43BF	2.3	6.4	4.8	16.1	10	4.3
	53BF	2.3	8.5	4.8	16.2	10	5.3
	65BF	2.3	11.0	4.8	20.1	10	6.5
4-6 (12 - 10)	37YF	3.5	6.4	6.5	20.8	13.5	3.7
	43YF	3.5	7.1	6.5	21.0	13.5	4.3
	53YF	3.5	9.5	6.5	21.6	13.5	5.3
	65YF	3.5	12.0	6.5	24.9	13.5	6.5

Pack Quantity: 100

Vibration resistant versions available on request
Non-insulated & Non-insulated High
Temperature Terminals available on request.