


Adrina



- High specification linear luminaire suitable for education, commercial and large retail applications
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort (AADRINA5 only)
- Supplied bi-directional light output as standard (directional only option can be selected if required)
- CCT selectable between 3000K and 4000K
- Suitable for individual or continuous surface or suspension mounting
- Dimmable and OCTO options available
- Powered by Tridonic



(AADRINA5 only)



Powered by
CASAMBI



AADRINA5 fitted with
AADRINA/SK

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	-20°C to 45°C	L70 50,000	80	3	90°	1	IP20

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR
AADRINA5	1500mm - CCT Selectable	27W	3000K/4000K	3600lm (4000K)	130lm/W (4000K)	19
AADRINA2X5	1500mm - CCT Selectable HO	50W		6800lm (4000K)		20

* UGR Value based on (4H - 8H)

CODE (OPTIONS)	DESCRIPTION
/SM3	Self-Test Emergency
/OCTO	OCTO Smart Control
/DD	Digital Dimming (DD1/DD3/DD4)

CODE (ACCESSORIES)	DESCRIPTION
AADRINA/SK	Adrina Suspension Kit
AADRINA/SMK	Adrina Surface Mounting Kit
AADRINA/600	Adrina Infill 600mm