

# Astro LED CCT

Supplied c/w Integral Driver and Trim Accessory



AALED1/BV/CCT  
(Fitted with Trim Attachment)




AALED1/WV/CCT




AALED2/WV/CCT  
(Fitted with Trim Attachment)

- All polycarbonate multi-purpose LED square bulkhead
- LED performance exceeds CFL equivalents
- Push fit feed-in, feed-out terminals for speed and ease of installation
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Instant light output and unlimited switching
- LED lifespan L70 56,000 hours



AALED1/CCT



AALED2/CCT

## LED Information

Total (Watts)	7W / 14W	
Lumens Delivered	4000K	3000K
7W	655lm	606lm
14W	1269lm	1170lm
Lm/W 7W	94lm	87lm
Lm/W 14W	91lm	84lm
CRI	Ra 80	
CCT	4000K	3000K
Input	230V	
Hertz	50Hz	
Operating Temp	-10°C to 25°C	

Code	Lamp	Description
AALED1/BV/CCT	LED	7W - Cool White/Warm White - Black Base, Visiluxe Cover
AALED1/WV/CCT	LED	7W - Cool White/Warm White - White Base, Visiluxe Cover
AALED2/BV/CCT	LED	14W - Cool White/Warm White - Black Base, Visiluxe Cover
AALED2/WV/CCT	LED	14W - Cool White/Warm White - White Base, Visiluxe Cover

Options	/PC	Electronic Photocell
	/M3	Emergency (14W only)
	/MWS	Integral Microwave Sensor (14W only)

