

LED Drivers

Constant Voltage Non-Dimmable



Constant Voltage 12V



AD30W/12V



AD75W/12V

Constant Voltage 24V / 48V



ADK15W/24V



ADK60W/24V



ADK120W/24V



ADK75W/48V

- Constant voltage non-dimmable drivers for 12V, 24V and 48V LED applications
- Thermal, short circuit and overload protection

	Code	Description	A	B	C
12V	AD30W/12V	30W	166	24	52
	AD75W/12V	75W	180	30	52
24V	ADK15W/24V	15W	123	45	19
	ADK60W/24V	60W	180	52	36
	ADK120W/24V	120W	300	40	30
48V	ADK75W/48V	75W	180	52	30

A = Length B = Height C = Width





• **JOINTS**

Easy fast-fit range of plug-in connections



ACLED/90



ACLED/TC



ACLED/90/FB



ACLED/XC

• **ACLED/RC/TOUCH**

Visible colour spectrum for easy finger touch control. Memory function for colour, mode, speed and brightness. RF up to a maximum of 20 metres




ACLED/RC/TOUCH



ACLED/RC/AMP

• **ACLED/AMP/TOUCH**

RGB Amplifier (Repeater) for use with ACLED/RC/TOUCH. Repeater(s) can be added to synchronise larger installations (one per 5 metre length required)



Link Lead Connection

Code	Lamp	Description
ACLED/90B		90° Bend
ACLED/90/FB		90° Flat Bend
ACLED/TC		T Connector
ACLED/XC		X Connector
ACLED100/LL		100mm Link Lead (White and RGB)
ACLED500/LL		500mm Link Lead (White and RGB)
ACLED1000/LL		1000mm Link Lead (White and RGB)
ACLED/ML		1000mm Mains Lead
ACLED/ML/RGB		1000mm Mains Lead RGB
ACLED/RC/TOUCH		Touch RGB RF Remote Control
ACLED/AMP/TOUCH		Touch RGB Amplifier (Repeater)
Accessories	AD30W/12V	30W 12V Constant Voltage Driver
	AD75W/12V	75W 12V Constant Voltage Driver
	ADDIM75W/12V	75W 12V Dimmable (1-10V or Switch Dim)





• **JOINTS**

Easy fast-fit range of plug-in connections



ACLED/90



ACLED/TC



ACLED/90/FB



ACLED/XC

• **ACLED/RC/TOUCH**

Visible colour spectrum for easy finger touch control. Memory function for colour, mode, speed and brightness. RF up to a maximum of 20 metres




ACLED/RC/TOUCH



ACLED/RC/AMP

• **ACLED/AMP/TOUCH**

RGB Amplifier (Repeater) for use with ACLED/RC/TOUCH. Repeater(s) can be added to synchronise larger installations (one per 5 metre length required)



Link Lead Connection

Code	Lamp	Description
ACLED/90B		90° Bend
ACLED/90/FB		90° Flat Bend
ACLED/TC		T Connector
ACLED/XC		X Connector
ACLED100/LL		100mm Link Lead (White and RGB)
ACLED500/LL		500mm Link Lead (White and RGB)
ACLED1000/LL		1000mm Link Lead (White and RGB)
ACLED/ML		1000mm Mains Lead
ACLED/ML/RGB		1000mm Mains Lead RGB
ACLED/RC/TOUCH		Touch RGB RF Remote Control
ACLED/AMP/TOUCH		Touch RGB Amplifier (Repeater)
Accessories	AD30W/12V	30W 12V Constant Voltage Driver
	AD75W/12V	75W 12V Constant Voltage Driver
	ADDIM75W/12V	75W 12V Dimmable (1-10V or Switch Dim)



Axiom LED Linear Plug and Play Rigid Strip

Supplied Less Driver

166



- Ultra slim profile rigid linkable LED strip
- Suitable for continuous illumination to a maximum of 5 metres
- Protective front cover
- Supplied with metal flush fixing clips
- LED lifespan L70 40,000 hours

Note:
Mains lead (AAXLED/ML) ordered separately



	Code	Lamp	Description	Length	Width	Depth
Cool White	AAXLED/30/CW	LED	4W-Cool White	300	20	12
	AAXLED/50/CW	LED	7W-Cool White	500	20	12
	AAXLED/90/CW	LED	12W-Cool White	900	20	12
Warm White	AAXLED/30/WW	LED	4W-Warm White	300	20	12
	AAXLED/50/WW	LED	7W-Warm White	500	20	12
	AAXLED/90/WW	LED	12W-Warm White	900	20	12
Accessories	AAXLED/ML		1500mm Mains Lead			
	AAXLED/250LL		250mm Link Lead			
	AAXLED/500LL		500mm Link Lead			
	AAXLED/1000LL		1000mm Link Lead			
	AD30W/12V		30W 12V LED Driver			
	AD75W/12V		75W 12V LED Driver			
	ADDIM75W/12V		75W 12V Dimmable (1-10V or Switch Dim)			

LED Information

	Cool White	Warm White
Total (Watts)	4W	7W
		12W
Lumens Delivered	282lm	284lm
	460lm	454lm
	791lm	830lm
Lm/W 4W	71lm	71lm
Lm/W 7W	66lm	65lm
Lm/W 12W	66lm	69lm
CRI	Ra 60	
CCT	5500K	
	3000K	
Input	12V DC	
Hertz	50/60Hz	
Operating Temp	-20°C to 45°C	

