

# PRODUCT DATA SHEET

## Ansell Lighting ADIS2/1/CF



### Disco EVO 2 Corridor Function

Manufacturer: Ansell Lighting

GTIN: 5056144292868

Family: [Display]

Range: Disco EVO



## DESCRIPTION

Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas

- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- High efficiency up to 145lm/W
- All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation
- Two options of microwave sensor emergency
- Instant light output and unlimited switching



TECHNICAL SPECIFICATION



ETIM Class: Ceiling / wall luminaire (EC002892)

Primary Features

|                       |                     |                          |    |
|-----------------------|---------------------|--------------------------|----|
| Lamp cap/base         | Other               | Maximum system power (W) | 49 |
| Light source included | Yes                 | Voltage type             | AC |
| Light source type     | LED non-replaceable |                          |    |

## Additional Features

|                                                                            |                             |                                                                                  |           |
|----------------------------------------------------------------------------|-----------------------------|----------------------------------------------------------------------------------|-----------|
| Beam angle                                                                 | Open beam/diffuse           | Flickering value Pst LM                                                          | 8         |
| Beam angle adjustable                                                      | No                          | Height/depth (mm)                                                                | 80        |
| Bluetooth operated                                                         | No                          | Housing material                                                                 | Plastic   |
| Colour consistency (McAdam ellipse)                                        | SDCM5                       | IFTTT support available                                                          | No        |
| Compatible with Amazon Alexa                                               | No                          | Impact resistance (IK rating)                                                    | IK08      |
| Compatible with Apple HomeKit                                              | No                          | Light diffuser type                                                              | Diffuser  |
| Compatible with Google Assistant                                           | No                          | Light distribution                                                               | Symmetric |
| Constant luminous flux control                                             | No                          | Lumen setting adjustable                                                         | No        |
| Control gear                                                               | LED driver constant current | Luminaire may be covered with thermally insulating material                      | No        |
| Control gear included                                                      | Yes                         | Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No        |
| Dimming 0-10 V                                                             | No                          | Outer diameter (mm)                                                              | 325       |
| Dimming 1-10 V                                                             | Yes                         | Power factor                                                                     | 5         |
| Dimming DALI                                                               | No                          | Protection class according to IEC 61140                                          | II        |
| Dimming DMX                                                                | No                          | Rated life time L70/B50 at 25 °C (h)                                             | 50000     |
| Dimming DSI                                                                | No                          | Recess diameter (mm)                                                             | 325       |
| Dimming leading edge                                                       | No                          | Recess height/depth (mm)                                                         | 80        |
| Dimming mains voltage modulation                                           | No                          | Replaceable control gear                                                         | Yes       |
| Dimming manufacturer's proprietary system                                  | No                          | Stroboscope effect value SVM                                                     | 3         |
| Dimming potentiometer (integrated)                                         | No                          | Suitable for ceiling mounting                                                    | Yes       |
| Dimming programmable                                                       | No                          | Suitable for emergency lighting                                                  | No        |
| Dimming RF                                                                 | No                          | Suitable for light line configuration                                            | No        |
| Dimming Touch and Dim                                                      | No                          | Suitable for surface mounting                                                    | Yes       |
| Dimming trailing edge                                                      | No                          | Suitable for suspended mounting                                                  | No        |
| Dimming with push-button                                                   | No                          | Unified Glare Rating (UGR)                                                       | 26        |
| Dimming Zigbee                                                             | No                          | With air slots                                                                   | No        |
| Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%) | 50                          | With light sensor                                                                | No        |
| Fit for workplace acc. EN 12464-1                                          | No                          | With movement sensor                                                             | No        |

## FURTHER DETAILS

Product Status (at download): Active

Date Updated: 15-07-2025

Trade Tariff Commodity Code: 9405114090

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD



☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

## Disclaimer

- This Data Sheet was downloaded from EDATA - [www.edata.org.uk](http://www.edata.org.uk) - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 09/10/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.