



- All polycarbonate multi-purpose LED round bulkhead
- LED performance exceeds CFL equivalents
- Push fit feed-in, feed-out terminals for speed and ease of installation
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Instant light output and unlimited switching
- LED lifespan L70 56,000 hours



ADLED1/CCT



ADLED2/CCT

LED Information

Total (Watts) 6W / 14W		
Lumens Delivered	4000K	3000K
	6W	670lm
	14W	1271lm
Lm/W 6W	112lm	105lm
Lm/W 14W	91lm	85lm
CRI	Ra 80	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50Hz	
Operating Temp	-10°C to 25°C	



Delta LED CCT

Supplied c/w Integral Driver and Trim Accessory



325



ADLED1/BV/CCT



ADLED1/WV/CCT
(Fitted with Trim Attachment)



ADLED2/BV/CCT
(Fitted with Louvred Bezel Trim)

Code	Lamp	Description
ADLED1/BV/CCT	LED	6W - Cool White/Warm White - Black Base, Visiluxe Cover
ADLED1/WV/CCT	LED	6W - Cool White/Warm White - White Base, Visiluxe Cover

ADLED2/BV/CCT	LED	14W - Cool White/Warm White - Black Base, Visiluxe Cover
ADLED2/WV/CCT	LED	14W - Cool White/Warm White - White Base, Visiluxe Cover

Options	/PC	Electronic Photocell
	/M3	Emergency (14W only)
	/MWS	Integral Microwave Sensor (14W only)

Accessories	ADLED2/BZ/EYE/B	Black Eyelid Bezel Trim (14W Only)
	ADLED2/BZ/EYE/W	White Eyelid Bezel Trim (14W Only)
	ADLED2/BZ/GRILL/B	Black Louvred Bezel Trim (14W Only)
	ADLED2/BZ/GRILL/W	White Louvred Bezel Trim (14W Only)

