

# PRODUCT DATA SHEET

## Ansell Lighting AHPTLED/1

### Helix CCT Post Top 1

Manufacturer: Ansell Lighting

GTIN: 5056144246656

Range: Helix

Family: Floodlighting



## DESCRIPTION

Modern die-cast aluminium post top lantern Ideal for large car parks and large open areas

- CCT selectable between 3000K and 4000K
- Electrostatic paint finish for enhanced corrosion resistance
- Advanced lens technology providing optimum performance and control.
- Suitable for residential and commercial use
- 76mm spigot bracket

## TECHNICAL SPECIFICATION

**ETIM Class: Street lighting (EC000062)**



### Primary Features

Colour of light	White	Luminaire efficacy (lm/W)	116
Colour temperature (K)	3000 - 4000	Maximum system power (W)	40
Degree of protection (IP rating)	IP66	Nominal voltage (V)	230 - 230
Lamp included	Yes	Number of lamps	1



## Additional Features

Colour consistency (McAdam ellipse)	SDCM5	Impact resistance (IK rating)	IK08
Colour rendering index (CRI/Ra)	70-79	Mounting method	Post-top
Control gear included	Yes	No dimming function	Yes
Diameter (mm)	450	Protection class	I
Height/depth (mm)	526	Surface protection	Other
Housing material	Aluminium		

## FURTHER DETAILS

Product Status (at download): Active

Date Updated: 16-05-2023

Trade Tariff Commodity Code: 9405423990

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

## Disclaimer

- This Data Sheet was downloaded from EDATA - [www.edata.org.uk](http://www.edata.org.uk) - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 17/10/2023.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.