



Onix LED Street Light

Supplied c/w Integral Driver



- Die-cast aluminium construction for optimal heat dissipation and performance
- UV stabilized polycarbonate cover
- Toolless gear tray removal for ease of maintenance
- Built in anti-tamper isolation facility
- Compatible with post top or side entry utility 76mm spigot
- G3 Glare Rating
- Surge protection
- Available in standard, complete with photocell option
- LED lifespan L70 50,000 hours



431



AONIXLED/1 - AONIXLED/2



AONIXLED/3 - AONIXLED/4



AONIXLED/1 - AONIXLED/2



AONIXLED/3 - AONIXLED/4



Adjustable 48-60mm Spigot bracket

LED Information

Total (Watts)	20W	60W
	40W	80W
Lumens Delivered	1974lm	6167lm
	3936lm	8222lm
Lm/W	104lm	103lm
	98lm	103lm
CRI	Ra 70	
CCT	5000K	
Input	100/240V	
Hertz	50Hz	
Operating Temp	-20°C to 50°C	

Code	Lamp	Description	Windage
AONIXLED/1	LED	20W - Cool White	0.04
AONIXLED/2	LED	40W - Cool White	0.04
AONIXLED/3	LED	60W - Cool White	0.07
AONIXLED/4	LED	80W - Cool White	0.07

Options	/PC	Electronic Photocell
---------	-----	----------------------

Accessories	AONIXLED/SBA	48-60mm Spigot Bracket
	AONIXLED/WB	Wall Bracket



Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750

