




# OCTO Prism Pro Fire Rated Connected by WIZ

OCTO Prism Pro Fire Rated Downlight Connected

Code: APRIP/1/OCTOW/TW

|               |                                             |
|---------------|---------------------------------------------|
| Category      | Downlights                                  |
| Application   | Ancillary, Hospitality, Residential, Retail |
| Specification | Architectural                               |



## PRODUCT FEATURES

- IP65 Dimmable LED WIZ enabled tunable white Fire Rated Downlight suitable for residential and commercial applications
- Tunable between 2700K - 6500K via WIZ app and voice control offering a choice of 2 outputs, in one luminaire
- Remote driver with 2x1.5mm + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- Connects directly to your WiFi network using Bluetooth technology to support seamless pairing
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Low profile design and remote driver allows installation into shallow ceiling voids
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations

## GENERAL INFORMATION

|                                  |                                 |
|----------------------------------|---------------------------------|
| Wattage                          | 8W                              |
| Lumens Delivered                 | 690lm - 680lm (2700K - 6500K)   |
| Lm/W                             | 92lm/w - 90lm/w (2700K - 6500K) |
| Beam Angle                       | 65                              |
| CRI                              | 80                              |
| CCT                              | 2700-6500K                      |
| Input                            | 220/240V                        |
| Operating Temp                   | -20°C - 35°C                    |
| SDCM                             | 6                               |
| UGR                              | 25                              |
| Cut-Out Size                     | 73mm                            |
| Product Weight without Packaging | 0.305 kg                        |

## TECHNICAL INFORMATION

|                                |             |
|--------------------------------|-------------|
| Light Source                   | LED         |
| Colour / Finish                | White       |
| Fire Rated                     | Yes         |
| IP Rating                      | IP65        |
| Class Protection               | 2           |
| Internal / External            | Internal    |
| Surface / Recessed / Suspended | Recessed    |
| Lumen Depreciation             | L70 60,000h |
| Warranty (Years)               | 5           |
| CE Mark                        | Yes         |
| Diameter                       | 90 mm       |
| Height                         | 58 mm       |

