


Z LED PERFORMANCE



- Robust, high efficacy, LED low/high bay for industrial, commercial and retail applications
- CCT selectable between 4000K, 5000K and 6500K
- Intelligent plug and play emergency pack option offers a quick and simple conversion from standard to emergency highbay
- Plug and play microwave and PIR sensor options, offering maximum energy saving
- Die-cast powder coated construction and heatsink for optimum thermal and performance
- Alternative installation options by means of jack chain and catenary wire
- Additional 55° narrow lens option ideal for racking aisles
- Bracket accessories available for ceiling or wall mounting
- Pre-wired with 1.5M of H07RN-F cable for ease and speed of installation
- 1-10V dimmable as standard
- Integrated 6kV surge protection



Powered by
CASAMBI

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
220/240V	50/60Hz	-20°C to 40°C	L90 50,000	80	6	120°	1	IP65	IK10

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	A	B
AZLP1/1		100W		18000lm		255mm	124mm
AZLP2/1	CCT Selectable	150W	4000K/5000K/6500K	27000lm	180lm/W	310mm	130mm
AZLP3/1		200W		36000lm		355mm	135mm

CODE (OPTIONS)	DESCRIPTION	CODE (OPTIONS)	DESCRIPTION
/DD	Digital Dimming (DD3)	/OCTO	OCTO Smart Control

CODE (ACCESSORIES)	DESCRIPTION	CODE (ACCESSORIES)	DESCRIPTION
AHHB/1	Hawk Highbay Emergency Kit	AZLP1/REF/1	Z LED Performance 1 Aluminium Reflector
AZLP/MWS	Z LED Performance Plug-in MWS Sensor	AZLP2/REF/1	Z LED Performance 2 Aluminium Reflector
AZLP/PIR	Z LED Performance Plug-in PIR Sensor	AZLP3/REF/1	Z LED Performance 3 Aluminium Reflector
AZLP/P	Z-LED Performance Sensor Programmer	AZLP1/L55	Z-LED Performance 1 High Bay 55° Lens
AZLP/FB1/1	Z LED Performance 1 Mounting Bracket	AZLP2/L55	Z-LED Performance 2 High Bay 55° Lens
AZLP/FB2/1	Z LED Performance 2 Mounting Bracket	AZLP3/L55	Z-LED Performance 3 High Bay 55° Lens
AZLP/FB3/1	Z LED Performance 3 Mounting Bracket		