

Technical Specification



Product Code: UDTAKIT Assistance Alarm Kit Description:



Part 2: Power, Light, and Buzzer Module

Part 1: Pull Cord Module

General Information		Power Supply	12VDC
Indication	LED illuminates in red when in alarm state	Power Consumption	0.3W
Buzzer	>80db when in alarm State	Indicator	LED illuminates red when in alarm state
Wire Gauge	1.5mm	Material	Anti-Microbial ABS
Inputs		Colour	White
Input Type	Ground & 2 live circuits - X1 & X2	Pull Cord Length	3 Meters, with 2 triangular bangles
Activation Type	Energise with a Normally Open Clean contact	Dimensions	Single gang; 87mm x 87mm x 41mm
Purpose	Activation and Reset Circuits		
Construction			
Material	Anti-Microbial ABS		
Fixing	Surface Only	Part 3: Reset Module	
Colour	White	Power Supply	12VDC
Outputs		Power Consumption	0.3W
Number of outputs	2	Indicator	LED illuminates red when in alarm state
Output Type	1 Switched Live sharing common ground	Material	Anti-Microbial ABS
	Separate output for additional sounders	Colour	White
Output Rating	12V500mA	Buzzer	>80db when in alarm state
Power		Dimensions	Single gang; 87mm x 87mm x 41mm
	100 ~ 230VAC	Supplied	
Consumption	0.2A	3 x Backboxes	
Battery Backup	A23 Battery	Installation Bolts	
Environment		Disabled sticker	
Ingress Protection	IP20	A23 Battery	
Dimensions	Single Gang; 87mm x 87mm x 41mm	User Manual	
Features		OSCI Mandai	

Built in Battery Backup with supplied A23 Battery Sounder buzzes intermittantly when battery needs replacing Anti-Microbial Properties

Accessories

UDTAPLBM	Assistance Alarm, Power, Light and Buzzer Module	
UDTALBM	Assistance Alarm Light and Buzzer Module	
UDTAPCM	Assistance Alarm Pull Cord Module	
UDTASPC	Assistance Alarm Replacement Pull Cord	
UDTAREM	TAREM Assistance Alarm Reset Module	

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 E: info@espuk.com | W: espuk.com

Page 1 of 1 Rev.1 Errors & Omissions excluded. Specification is subject to change without notice.